

# water heater



## Purpose

The PORTAheater 75 is a portable high flow rate water heater specifically designed to supply tepid water for improved cleansing and decontamination action.

### Technical Data

- Water Output temp: 20-45°C
- Nominal voltage: 110V
- Inlet connection: 1" brass female cam-lock
- Outlet connection: 2 x ¾" brass male cam-lock
- Handling: 2 wheels + 3 adjustable handles
- Dimensions  
L 0.825m x W 0.54m x H 0.745m
- Dry Weight: 110kg



## Features & Benefits

- Capability to heat cold water from a pressure of between 1 and 5 bar at a flow rate of 75 litres per minute
- Detachable insulated stack exhaust
- Single start switch operation
- Trolley frame mounted to allow easy handling and movement of the unit
- Cold water inlet is fitted with a flow regulator with integral filter
- Dual outlets with thermostat control
- Built in non-return valve
- Corrosion resistant piping
- 110v IP67 electrical socket is fitted for connection to a generator
- Flow switch control in the event of a supply pressure drop below 1 bar
- Over pressure release valve
- Extra cold water outlet incorporated
- Thermometer supplied for external monitoring
- Retractable fuel supply hose with quick release fitting
- Low point water drain valve
- 10cm ground clearance and solid rubber tyres
- Health & safety, controls and switch labelling
- Mild steel powder coated frame
- Running time of 5 hours with a tank capacity of 20 litres

## Now there's a better way

